

# level ten collection


property management seamless flooring



## Designs



Washington | 596B  
U9480.212K596G144



Boston | 845  
U2720.212K845G144



Koala | 746  
U5030.212K746G144



Nice | 793  
U1070.212K793G144



Condor | 535A  
U3140.212K535G144



Arezzo | 504  
U3700.212K504G144



Baron | 713  
U6580.212K713G144



Koala | 715  
U5030.212K715G144

# level ten collection

property management seamless flooring



## Designs



Aspin | 551  
U3890.212K551G144



Sandbridge Slate | 594  
U5330.212K594G144



Condor | 564A  
U3140.212K564G144



Condor | 573  
U3140.212K573G144



Majestic Oak | 895  
U9540.406K895G144



Arcadia | 739  
U6040.212K739G144

# level ten collection

property management seamless flooring



## Specifications

Construction	Recommended Usage	Thickness	Wear Layer	Wear Layer Treatment	Finish	Width	Standard Length	Average Weight of Standard Roll	Warranty
Sheet Vinyl	Residential	55 Gauge	10 mil	QuickClean	Mechanically Embossed	12'	150 lineal ft	456.2 lbs	5-Year Property Management*

\* See written limited warranty for full details.

## Testing Information

ASTM 1303.....	Type 1, Grade 3
Residual Indentation   ASTM F1914.....	006
Flexibility   ASTM F137.....	Passes (10 mm)
Resistance to Heat   ASTM F1514.....	Passes
Resistance to Light   ASTM F1515.....	Passes
Resistance to Chemicals   ASTM F925.....	Very Good
Sound Transmission/Impact Insulation   ASTM E492.....	IIC 54
Critical Radiant Flux   ASTM E648.....	Class I
Static Coefficient of Friction   C1028-96.....	Passes (Dry .77/Wet .61)
Smoke Density (flaming)   ASTM E662-03.....	Passes 450 or less
Smoke Density (non-flaming)   ASTM E662-09.....	Passes 450 or less



# level ten collection

property management seamless flooring



## Adhesives

- **Flex-Tech PSA for Sheet Vinyl**

**1 Gallon** 706471 | **4 Gallon** 706472 | **1 Quart** 706473

**Coverage** 250 sq ft/gallon - porous | 350 sq ft/gallon - non porous

Pressure sensitive adhesive | Clear set | Solvent free

- **Flex-Seam Bond**

**8 oz.** 706474

Solvent free | Low VOC | High strength | Fast drying | Dries clear

- **Flex-Prim Acrylic Latex Primer**

**1 Gallon** 706475

**Coverage** Up to 500 sq ft/gallon

Use as primer coat | Increases adhesive performance | Increases adhesive coverage



**Medallion**

[www.medallion1.com](http://www.medallion1.com)

2434 Polvorosa Ave., San Leandro CA 94577, Ph.: 510-351-8104 Fax: 510-483-4874  
839 F Street, Suite 100, West Sacramento CA 95605 Ph.: 916-372-8501, Fax: 916-372-2175  
645 Ahua Street, Honolulu HI 96819, Ph.: 808-836-3585, Fax: 808-834-4722