

# level plus collection


property management seamless flooring



## Designs



Charlton | 736  
U9775.119K736P144



Manday | 875  
U8205.119K875P144



Manday | 876  
U8205.119K876P144



Chatham | V94  
U9785.119KV94P144



Morgane | 535  
U5970.119K535P144



Kendall | 597  
U9880.119K597P144



Kahlo | 592  
U9695.119K592P144



Bongo | 847  
U3950.119K847P144



# level plus collection

property management seamless flooring



## Designs



Bodega | 540  
U0215.119K540P144



Brisbane | 933  
U5110.119K933P144



Lorraine | 595  
U9870.119K595P144



Bonnette | 934  
U6160.119K934P144




Nice | 858  
U1070.119K858P144




Ashland | 893  
U9470.119K893P144



Charlton | 792  
U9775.119K792P144



Luxor | 892  
U2360.228K892P144



Preston | 542  
U2360.228K892P144

# level plus collection

property management seamless flooring



## Specifications

Construction	Recommended Usage	Thickness	Wear Layer	Wear Layer Treatment	Finish	Width	Standard Length	Average Weight of Standard Roll	Warranty
Sheet Vinyl	Residential	65 Gauge	10 mil	SuperGuard	Mechanically Embossed	12'	150 lineal ft	520 lbs	10-Year Property Management*

\* See written limited warranty for full details.

## Testing Information

ASTM 1303.....	Type 1, Grade 3
Residual Indentation   ASTM F1914.....	006
Flexibility   ASTM F137.....	Passes (10 mm)
Resistance to Heat   ASTM F1514.....	Passes
Resistance to Light   ASTM F1515.....	Passes
Resistance to Chemicals   ASTM F925.....	Very Good
Sound Transmission/Impact Insulation   ASTM E492.....	IIIC 55
Critical Radiant Flux   ASTM E648.....	Class I
Static Coefficient of Friction   C1028-96.....	Passes (Dry .81/Wet .79)
Smoke Density (flaming)   ASTM E662-03.....	Passes 450 or less
Smoke Density (non-flaming)   ASTM E662-09.....	Passes 450 or less



# level plus collection

property management seamless flooring



## Adhesives

- **Flex-Tech PSA for Sheet Vinyl**

**1 Gallon** 706471 | **4 Gallon** 706472 | **1 Quart** 706473

**Coverage** 250 sq ft/gallon - porous | 350 sq ft/gallon - non porous

Pressure sensitive adhesive | Clear set | Solvent free

- **Flex-Seam Bond**

**8 oz.** 706474

Solvent free | Low VOC | High strength | Fast drying | Dries clear

- **Flex-Prim Acrylic Latex Primer**

**1 Gallon** 706475

**Coverage** Up to 500 sq ft/gallon

Use as primer coat | Increases adhesive performance | Increases adhesive coverage



# Medallion

[www.medallion1.com](http://www.medallion1.com)

2434 Polvorosa Ave., San Leandro CA 94577, Ph.: 510-351-8104 Fax: 510-483-4874  
839 F Street, Suite 100, West Sacramento CA 95605 Ph.: 916-372-8501, Fax: 916-372-2175  
645 Ahua Street, Honolulu HI 96819, Ph.: 808-836-3585, Fax: 808-834-4722