



 SPECIFICATION DATA

Style Name:	SPECIFIER 26
Style Number:	752P3
Description:	TEXTURED LOOP
Fiber Content:	100% SOLUTION Q NYLON
Tufted Weight:	26.0 ozs/yd ²
Finished Pile Thickness:	0.132 in
Total Thickness:	0.286 in
Gauge:	1/8
Tufts:	7 per in
Primary Backing:	SYNTHETIC
Secondary Backing:	CLASSICBAC
Total Weight:	60 ozs/yd ²
Density:	7091 ozs/yd ³
Twist Information:	
Width:	12 ft
Number of Colors:	13
Dye Method:	SOLUTION DYED
Coefficient of Friction:	0.84
Applications:	
Pattern Repeat:	NONE
Star Rating:	
Special Features:	

 PRODUCT DATA

Flammability:

Pill Test (CPSC FF1-70):	PASS
Flooring Radiant Panel (ASTM E-648) Direct Glue:	Class I
NBS Smoke Density : ASTM-E662	
Flaming Mode:	< 450
Non-Flaming Mode:	< 450
Static:	
AATCC-134:	< 3.5 KV
Type Static Control:	PERMANENT CONDUCTIVE FIBER
FHA DATA UM44D Certification Number:	77461
Type:	I
Class:	1
Texture:	A

Warranties:

10 YEAR COMMERCIAL LIMITED WARRANTY FOR CLASSICBAC PRODUCTS
 SOLUTION Q SDN WARRANTY

CRI Certification:	16908472
Green Label Plus:	GLP8472
TARR Rating: 3.00	
Green Lable Plus:	GLP8472
Recommended Traffic Class:	HEAVY

Except where noted as a minimum or maximum, the above specifications are nominal and, therefore, are subject to change and to normal manufacturing variance.